






REV.	DESCRIPTION	DATE	DRAFTER	APPROVER
V1.0	DWG.REL	2024.12.27	ZHANG	JIN



- Material
 - ØScrew : M4.0, Steel, Zinc plated
 - ØTerminal : Copper alloy, Tin plated
 - ØHousing : PBT
 - ØNut : Steel, Zinc plated
- Electrical
 - Rated voltage : 600V
 - Rated current : 30A
 - Contact resistance : 20mΩ(Max)
 - Insulation resistance : 500MΩ/DC500V
 - Withstanding Voltage : AC3000V/1min
- Mechanical
 - Operating temperature: -40°C~+105°C
 - Torque : 1.5N.m (15.3kgf.cm)
 - Wire range: 16-12AWG;1.5-4.0mm²
- Conform to REACH and RoHS



HOW TO ORDER
 2KF033-11.0-XP-1 X-XXXXX
 MODEL Pitch:mm No. of poles: 3P
 X-XXXXX
 Customer Request
 Color:
 C:Green R:Red
 K:Black W:White
 O:Orange B:Blue
 GR:Gray
 1:Single Pitch
 2:Double Pitch

Pitch range	Nominal dimension range	PROJECTION	UNIT	TITLE
>0 ~6	>6 ~10 ~24	0.1/10	mm	2KF033-11.0-3P-1K
±0.15 ±0.20 ±0.30	±0.30 ±0.50 ±0.70 ±1.00 ±1.30		SHEET SIZE	A4 SERIES 2KF033
DRAWING TYPE		CUSTOMER DRAWING		
SCALE		1:1 SHEET 1 OF 1		
DRAWING NO.		W12006452		

DF 慈溪市凯峰电子有限公司
 CIXI KAIFENG ELECTRONICS CO.,LTD